

pE-300^{ultra} Controllable Optogenetics Illumination

TTL for control from your Electrophysiology rig

油油油油

CoolLED

pE-300**





www.CoolLED.com

pE-300 Controllable Optogenetics Illumination

Utilising the technology from CoolLED's very successful *p*E-300 Series, the *p*E-300^{ultra} includes the same broad spectrum coverage and highly usable LEDs as other members of the *p*E-300 Series which have been helping scientists carry out highly repeatable, consistent experiments for years. Added to this, the *p*E-300^{ultra} has the ability to filter precisely your stimulation wavelength as required and, via multiple TTL inputs, connects directly to your electrophysiology rig, stimulator and other hardware for integration with your whole system.

ultra

Cool

oE-300

- Stimulates popular opsins (ChR, HR)
- Precisely filters your stimulation wavelength as required utilising removable inline filter holders
- Connects to your electrophysiology rig, stimulator and other hardware via multiple TTL inputs
- Fits most microscopes as a wide range of microscope adaptors is available
- Delivers light through direct attachment or light guide for no unwanted vibration or electrical noise

- Is ideal for both Optogenetics applications and regular fluorescence microscopy allowing you to make more use of your microscopy set up
- Includes "Sequence Runner" multiple channel excitation mode. This offers users the facility to run through a sequence of excitation channels using a camera which has only a single TTL-out

The *p*E-300^{ultra}: Fast controllable illumination

w: www.CoolLED.com e: info@CoolLED.com